

Amy

VARIO

Recessed LED Downlight



Ideal for: Circulation corridors, reception areas, schools/universities and office/meeting rooms



Versatile and timeless, Amy is the ideal solution for a vast range of applications.




- VARIO Feature (Colour Temperature Switch): The ability to choose your colour temperature on site with the flick of a switch
- The fully detachable connector allows for first fix wiring and high voltage circuit testing whilst the luminaire is detached from the connector
- Save time with easy, tool-free installation
- Replacement for traditional 1×18W, 1×26W, 2×18W or 2×26W compact
- Suitable for use with phase-cut dimmer switches
- JUST: adapt on-site to an emergency version using the Just Emergency PLUG&PLAY kit



	∅	W1	W2	H1	H2	H3
AMY LED 100	100	120	95	55	18	9
AMY LED 150	150	170	140	69	25	9
AMY LED 200	200-240	250	190	79	30	9

Dimensions (mm)



Specification

Electrical class	II
Ambient operating temperature	-20 to +40 °C

Installation / Mounting

Mounting	Amy can be installed into a wide range of ceiling types of 2–20 mm thickness. Connector for tool-free wiring, also enabling loop-in loop-out
----------	----------------------------------------------------------------------------------------------------------------------------------------------

Material / Finish

Body	Steel, white finish (RAL 9003)
Diffuser	Polycarbonate

Light source information

VARIO (Colour temperature switch)	3000K, 3500K and 4000K
Lumen	700lm (7W), 1000lm (10W), 1500lm (15W), 2000lm (20W)
Efficiency	up to 100lm/W
Lifetime	50 000 hours (@L80, Ta 25 °C)
MacAdam (Initial)	4

Ordering guide

Description	SAP Code
AMY VARIO 100 LED DL 700 830/35/40	96632753
AMY VARIO 150 LED DL 1000 830/35/40	96632754
AMY VARIO 150 LED DL 1500 830/35/40	96632755
AMY VARIO 200 LED DL 2000 830/35/40	96632756
Accessories	
THORNeco Connector	96631101
Just E3 PLUG&PLAY Kit SelfTest LiFePO4	96634428
Just E3 PLUG&PLAY Kit ManualTest LiFePO4	96635766